

Fusion

GMSSV 52"H Refrigerated Self-Service Case

Structural Concepts®
DELIVERING FRESH. ALWAYS.™

- **GMSSV452R** 51"L x 43"D x 51-5/8"H
- **GMSSV552R** 62-7/8"L x 43"D x 51-5/8"H
- **GMSSV652R** 75-3/8"L x 43"D x 51-5/8"H
- **GMSSV852R** 99-3/4"L x 43"D x 51-5/8"H



GMSSV652R

- Included**
- Remote DX refrigeration
 - LED top & shelf lights
 - One year parts & labor warranty
 - Stainless steel rear exterior
 - Warmest average product temperature of 40°F or less

Specify	Standard Features	Additional Options
EXTERIOR COLOR	<ul style="list-style-type: none">• Laminate (stock colors)	<ul style="list-style-type: none">• Laminate (non-stock colors)• Powder coated (stock/non-stock colors)• Powder coated Silversan Black• Stainless steel
INTERIOR COLOR	<ul style="list-style-type: none">• Powder coated Silversan Black	<ul style="list-style-type: none">• Stainless steel
LOWER FRONT PANEL COLOR	<ul style="list-style-type: none">• Powder coated Silversan Black	<ul style="list-style-type: none">• Powder coated (stock/non-stock colors)• Stainless steel
BASE SUPPORT	<ul style="list-style-type: none">• Rail system for shims	
BUMPER FRONT	<ul style="list-style-type: none">• 1" Boston bumper (specify color)	<ul style="list-style-type: none">• 1" Stainless steel plate rail bumper
END PANELS	<ul style="list-style-type: none">• Full w/stainless steel mirror interior	<ul style="list-style-type: none">• Cutaway w/glass• None (specify per line-up)
PRICE TAG MOLDING	<ul style="list-style-type: none">• None	<ul style="list-style-type: none">• 1" Price tag molding (black or silver)• Universal price tag molding (clear w/ open top)
SHELVING	<ul style="list-style-type: none">• 16" & 20" Solid shelving	<ul style="list-style-type: none">• 16" & 20" Glass shelving
LIGHTS	<ul style="list-style-type: none">• LED 3500K w/ frosted lens	<ul style="list-style-type: none">• LED 4000K w/ frosted lens
ELECTRICAL CONNECTION	<ul style="list-style-type: none">• Electrical leads (remote)	
REFRIGERATION	<ul style="list-style-type: none">• Remote DX refrigeration	<ul style="list-style-type: none">• Remote w/thermostat, solenoid & TXV
SENSOR	<ul style="list-style-type: none">• None	<ul style="list-style-type: none">• CPC discharge air sensor (remote)
ACCESSORIES		<ul style="list-style-type: none">• Drain strainer• Night curtain, retractable, non-locking• Removable wire security cover, locking

Fusion

GMSSV 52"H Refrigerated Self-Service Case


Structural Concepts®

DELIVERING FRESH. ALWAYS.™


Intended Environment: Type I - Designed to operate in ambient conditions of 75°F with 55% relative humidity unless noted otherwise in system information below.

Zone	Intended Product To Be Displayed	Warmest Avg Prod Temp ° F
1	Packaged refrigerated products	40

PLAN VIEW



SIDE VIEW



NOTE: ALL DIMENSIONS APPROXIMATE

- ELECTRICAL JUNCTION BOX (SUPPLIED WITH 6\"/>

- REFRIGERATION LINE CONNECTION.
- REMOTE FLOOR SINK & UTILITIES ACCESS AREA.

- SELF-CONTAINED CASE SERVICE ACCESS AREA.
- DRY CASE SERVICE ACCESS AREA.

Model Technical Specifications														
Model	L"	L1"	L2"	System Circuit Volts			Phs	Freq	Amps ***	Watts	Wires	NEMA Plug	SST	Conv. Rack BTU/H
GMSSV452R	48.75	51.00	3.50	Remote (DX)	Circuit #1	110-120	1	60	1.18	86	2+G	Leads Multiple	20.00	3201
				Remote (R744 TRANSCRIT)	Circuit #1	110-120	1	60	1.18	149	2+G	Leads Multiple		2964
GMSSV552R	60.63	62.88	3.50	Remote (DX)	Circuit #1	110-120	1	60	1.54	81	2+G	Leads Multiple	24.00	3499
GMSSV652R	73.13	75.38	3.50	Remote (DX)	Circuit #1	110-120	1	60	2.54	131	2+G	Leads Multiple	20.00	5270
GMSSV852R	97.50	99.75	3.50	Remote (DX)	Circuit #1	110-120	1	60	3.03	274	2+G	Leads Multiple	20.00	6847

*** Does not include electric defrost on freezer models.

Regulatory Approvals:

All Models
 Accordance with AHRI Std 1200
 ETL Listed to UL 471
 ETL Listed to CAN/CSA 22.2 No. 120
 ETL Sanitation to NSF/ANSI 7



In Accordance with
AHRI Std 1200

DOE 2017
 Energy Efficiency
 Compliant

Important Notes:

- 1) ELECTRICAL NOTE: If GFCI is required, a GFCI breaker MUST be used in lieu of a GFCI receptacle
- 2) 45" minimum door entry clearance required (without shipping skid).
- 3) Units must be shimmed during installation to ensure the unit is level and plumb.

⚠ WARNING: This product can expose you to chemicals, including Urethane (Ethyl Carbamate), which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.