

- **MI32R** 26-1/8"L x 36-1/2"D x 39-1/8"H
- **MI33R** 38-1/8"L x 36-1/2"D x 39-1/8"H
- **MI36R** 74-1/8"L x 36-1/2"D x 39-1/8"H

Included

- Breeze self-contained refrigeration
- Casters
- Corrosion resistant stainless steel tub & fan shroud
- Integrated average product temperature adjustable from 38°F to 40°F
- One year parts & labor; 5 year compressor warranty
- Removable deck pans provide complete access to evaporator coil & refrigeration connections
- Solid metal deck
- Straight insulated glass ends




MI33R

Specify	Standard Features	Additional Options
EXTERIOR COLOR	• Powder coated Silversan Black	• Laminate (non-stock colors) • Laminate (stock colors) • Powder coated (stock colors, specify RAL#) • Stainless steel
INTERIOR COLOR	• Powder coated Silversan Black	• Stainless steel
BASE SUPPORT	• Powder coated Silversan Black	• Stainless steel (must choose stainless exterior)
BUMPER	• 1" bumper, double strip (specify color)	
ELECTRICAL CONNECTION	• 6' 90° Straight blade power cord (self-cont.)	• 6' Locking power cord (self-cont.)
EVAPORATOR COIL	• Non-coated evaporator coil	• E-Coated evaporator coil
THERMOMETER	• Digital fahrenheit thermometer	• Digital celsius thermometer
MISCELLANEOUS		• Second year parts & labor warranty (excludes compressor)
ACCESSORIES		¹ • Clean Sweep® coil cleaner (self-cont.) • Electrical drop cord cover (matches exterior color)


Option Notes: 1 - n/a on MI32R, MI33R

Intended Environment: Type I - Designed to operate in ambient conditions of 75°F with 55% relative humidity unless noted otherwise in system information below.		
Zone	Intended Product To Be Displayed	Warmest Avg Prod Temp ° F
1	Packaged raw meat (38°) Packaged produce/deli (40°)	38-40

PLAN VIEW



- ELECTRICAL JUNCTION BOX (SUPPLIED WITH 6" LEADS OR POWER CORD).
- LOCATION OF DRAIN TUBE FOR REMOTE REF. ONLY (SUPPLIED WITH 3/4" OR 1 1/2" PVC TUBE).




	"L3"	"L4"
MI32R	8"	3 5/8"
MI33R	7"	6 3/4"
MI36R	7"	8 3/4"

NOTE: ALL DIMENSIONS APPROXIMATE

- REFRIGERATION LINE CONNECTION.
- REMOTE FLOOR SINK & UTILITIES ACCESS AREA.
- SELF-CONTAINED CASE SERVICE ACCESS AREA.
- DRY CASE SERVICE ACCESS AREA.

SIDE VIEW



Model Technical Specifications

Model	L"	L1"	L2"	System Circuit Volts	Phs	Freq	Amps ***	Watts	Wires	NEMA Plug	SST	Conv. Rack BTUH	Para. Rack BTUH	Est Wt	
MI32R	N/A	26.13	7.00	Self-Contained (R513A)	Circuit #1	110-120	1	60	11.04	1,014	N/A	5-15P or L5-15P	N/A	N/A	650
MI33R	N/A	38.13	7.00	Self-Contained (R513A)	Circuit #1	110-120	1	60	9.35	801	2+G	5-15P or L5-15P	N/A	N/A	750
MI36R	N/A	74.13	7.00	Self-Contained (R513A)	Circuit #1	110-120	1	60	15.19	1,540	2+G	5-20P or L5-20P	N/A	N/A	950

*** Does not include electric defrost on freezer models.

Regulatory Approvals:

All Models
 Accordance with AHRI Std 1200
 ETL Listed to UL 471
 ETL Listed to CAN/CSA 22.2 No. 120
 ETL Sanitation to NSF/ANSI 7



In Accordance with
AHRI Std 1200

DOE 2017
 Energy Efficiency
 Compliant

Important Notes:

- ELECTRICAL NOTE: If GFCI is required, a GFCI breaker MUST be used in lieu of a GFCI receptacle
- Maximum load height is 8-1/4" up from deck.
- Compressor air side intake and side discharge. All louvered panels cannot be blocked.

⚠ WARNING: This product can expose you to chemicals, including Urethane (Ethyl Carbamate), which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.