

Fusion

GHSS 60"H Refrigerated Self-Service Case Self-Contained w/ Curved Profile

Structural Concepts®

DELIVERING FRESH. ALWAYS.™

• GHSS460R

51"L x 43"D x 59-5/8"H

Included

- Breeze self-contained refrigeration
- LED top & shelf lights
- One year parts & labor; 5 year compressor warranty
- Stainless steel rear exterior
- Warmest average product temperature of 40°F or less



GHSS460R

| Specify | Standard Features | Additional Options |
|--------------------------------|---|---|
| EXTERIOR COLOR | • Laminate (stock colors) | • Laminate (non-stock colors) • Powder coated (stock/non-stock colors) • Powder coated Silversan Black • Stainless steel |
| INTERIOR COLOR | • Powder coated Silversan Black | • Stainless steel |
| LOWER FRONT PANEL COLOR | • Powder coated Silversan Black | • Powder coated (stock/non-stock colors) • Stainless steel |
| BASE SUPPORT | • Casters w/ levelers (self-cont.) | • 6"H legs (self-cont.) |
| BUMPER FRONT | • 1" Boston bumper (specify color) | ¹ • 1" Stainless steel plate rail bumper |
| END PANELS | • Full w/stainless steel mirror interior | • Cutaway w/glass • None (specify per line-up) |
| SCALE STAND | • None | ² • Scale stand w/ receptacle & CAT5 (specify location) • Scale stand w/ receptacle (specify location) |
| PRICE TAG MOLDING | • None | • 1" Price tag molding (black or silver) • Universal price tag molding (clear w/ open top) |
| REAR DOORS | • None (solid back panel) | • Solid rear swinging doors |
| SHELVING | • 14" & 16" & 18" & 22" Solid shelving | • 14" & 16" & 18" & 22" Glass shelving |
| LIGHTS | • LED 3500K w/ frosted lens | • LED 4000K w/ frosted lens |
| ELECTRICAL CONNECTION | • 6' Straight blade power cord (self-cont.) | • 6' Locking power cord (self-cont.) |
| REFRIGERATION | • Breeze self-contained refrigeration | |
| MISCELLANEOUS | | • Rear door lock |
| ACCESSORIES | | • Clean Sweep® coil cleaner (self-cont.) • Drain strainer • Night curtain, retractable, non-locking • Removable wire security cover, locking |

Option Notes: 1 - 4ft;



2 - Separate circuit required

Intended Environment: Type I - Designed to operate in ambient conditions of 75°F with 55% relative humidity unless noted otherwise in system information below.

| Zone | Intended Product To Be Displayed | Warmest Avg Prod Temp ° F |
|------|---|---------------------------|
| 1 | Packaged refrigerated products-Prechilled to Warmest Avg Prod Temp. | 40 |

PLAN VIEW

SIDE VIEW



NOTE: ALL DIMENSIONS APPROXIMATE

- ELECTRICAL JUNCTION BOX (SUPPLIED WITH 6" LEADS OR POWER CORD).
- LOCATION OF DRAIN TUBE FOR REMOTE REF. ONLY (SUPPLIED WITH 3/4" OR 1 1/2" PVC TUBE).

- REFRIGERATION LINE CONNECTION.
- REMOTE FLOOR SINK & UTILITIES ACCESS AREA.

- SELF-CONTAINED CASE SERVICE ACCESS AREA.
- DRY CASE SERVICE ACCESS AREA.

Model Technical Specifications

| Model | L" | L1" | L2" | System | Circuit Volts | Phs | Freq | Amps *** | Watts | Wires | NEMA Plug | SST | Conv. Rack BTUH | Para. Rack BTUH | Est Wt | |
|----------|-------|-------|------|-----------------------|---------------|---------|------|----------|-------|-------|-----------|-----------------|-----------------|-----------------|--------|-------|
| GHSS460R | 48.75 | 51.00 | 3.50 | Self-Contained (R290) | Circuit #1 | 208-240 | 1 | 60 | 16.00 | 2,801 | 2+G | 6-20P or L6-20P | N/A | N/A | N/A | 1,100 |

*** Does not include electric defrost on freezer models.

Regulatory Approvals:

| | |
|------------|---|
| All Models | Accordance with AHRI Std 1200 ETL Listed to UL 471 ETL Listed to CAN/CSA 22.2 No. 120 ETL Sanitation to NSF/ANSI 7 |
|------------|---|



Important Notes:

- 1) ELECTRICAL NOTE: If GFCI is required, a GFCI breaker MUST be used in lieu of a GFCI receptacle
- 2) 45" minimum door entry clearance required (without shipping skid).
- 3) Units must be shimmed during installation to ensure the unit is level and plumb.

⚠ WARNING: This product can expose you to chemicals, including Urethane (Ethyl Carbamate), which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.