Millwork Requirements for Under Counter Oasis Cases

Structural Concepts®
DELIVERING FRESH. ALWAYS.™

MODEL	CASE WIDTH	CASE DEPTH	CASE HEIGHT	'A' CUTOUT FOR MERCHANDISING AREA DEPTH	'B' CUTOUT FOR MERCHANDISING AREA WIDTH	'C' CUTOUT FOR MERCHANDISING AREA HEIGHT	'D' MINIMUM REQUIRED OPENING
CN33R-UC	35-5/8"	26-1/4"	32-1/4"	14-5/8"	33-1/8"	13-3/8"	35-7/8"
CN43R-UC	47-5/8"	26-1/4"	32-1/4"	14-5/8"	45-1/8"	13-3/8"	47-7/8"
CN53R-UC	59-5/8"	26-1/4"	32-1/4"	14-5/8"	57-1/8"	13-3/8"	59-7/8"
C23R-UC	25-7/8"	34-1/4"	32-1/4"	14-5/8"	25-3/8"	13-3/8"	26-1/8"
C33R-UC	35-5/8"	34-1/4"	32-1/4"	14-5/8"	33-1/8"	13-3/8"	35-7/8"
C43R-UC	47-5/8"	34-1/4"	32-1/4"	14-5/8"	45-1/8"	13-3/8"	47-7/8"
C53R-UC	59-5/8"	34-1/4"	32-1/4"	14-5/8"	57-1/8"	13-3/8"	59-7/8"
C63R-UC	71-5/8"	34-1/4"	32-1/4"	14-5/8"	69-1/8"	13-3/8"	71-7/8"

Please Note

Minimum counter dimensions to be free of any obstructions

Power cord is in the rear of the case.

If adding front panel or lower front panels to millwork, they must not be attached to the case and easily removable for service.

Do not block intake or discharge air.

Do not block lower front panel or lower rear panel, full access is needed for service and proper airflow

Optional rear spacers are available. If used, add 2-5/8" to the case.





