

End Caps - BOX Heated Self-Service Case 32"D

| DIMENSIONS / SHIPPING | | | | |
|-----------------------|-----|--------|-------|--------------|
| Model | L" | L1" | L2" | Est Wt (lbs) |
| B2432H | N/A | 24.750 | 0.000 | 800 |
| B2432H-4 | N/A | 24.750 | 0.000 | 800 |
| B3632H | N/A | 36.750 | 0.000 | 1,000 |
| B3632H-4 | N/A | 36.750 | 0.000 | 1,000 |

| ELECTRICAL | | | | | | | | | | | | | | | | |
|------------|----------------------|------------|---------|---|----|-------|-----------------|--------------|--------------|-------|-----------------|-----------|-------------|-----------|------------------|-----------------------|
| Model | System Circuit Volts | | | | Ph | Frq | Rated Load Amps | Min Cir Amps | Max OCP Amps | Watts | Wires | NEMA Plug | Amps Lights | Amps Fans | Amps Anti-Sweats | Amps Misc/Refrig/Heat |
| B2432H | Heat | Circuit #1 | 208-240 | 1 | 60 | 13.91 | 20 | 20 | 2,942 | 2+G | 6-20P or L6-20P | 1.00 | 0.12 | N/A | 12.79 | |
| B2432H-4 | Heat | Circuit #1 | 208-240 | 1 | 60 | 15.30 | 20 | 20 | 3,252 | 2+G | 6-20P or L6-20P | 1.25 | 0.12 | 2.27 | 11.66 | |
| B3632H | Heat | Circuit #1 | 208-240 | 1 | 60 | 20.34 | 30 | 30 | 4,296 | 2+G | 6-30P or L6-30P | 1.00 | 0.18 | N/A | 19.16 | |
| B3632H-4 | Heat | Circuit #1 | 208-240 | 1 | 60 | 23.54 | 30 | 30 | 5,031 | 2+G | 6-30P or L6-30P | 2.50 | 0.18 | 10.42 | 10.44 | |

| REFRIGERATION | | | | | | | | | | | | | | | |
|---------------|------|---------|--------|------|----------------------|-----------------|-----------------|------------------------|-------------------------|-----------------------------|---------------------|-------------|------------------|--|--|
| Model | Zone | Section | System | Envt | REMOTE REFRIGERATION | | | | | GLYCOL / R744 REFRIGERATION | | | | | |
| | | | | | SST (°F) | Conv. Rack BTUH | Para. Rack BTUH | Defrost Interval (Hrs) | Defrost Duration (Mins) | Total GPM | Pressure Drop (psi) | Concent (%) | Liquid Temp (°F) | | |
| | | | | | | | | | | | | | | | |

| INTENDED ENVIRONMENT | | |
|--|-----------|-------------------------|
| Type I - Designed to operate in ambient conditions of 75°F with 55% relative humidity unless noted otherwise under Envt above. | | |
| WARMEST AVERAGE PRODUCT TEMP & INTENDED USE OF ZONES | | |
| Zone | Temp (°F) | Intended Use |
| 1 | 160 | Packaged heated product |

| IMPORTANT NOTES |
|--|
| 1) ELECTRICAL NOTE: If GFCI is required, a GFCI breaker MUST be used in lieu of a GFCI receptacle |
| 2) Performance issues (product temperatures, water on floor, etc.) caused by adverse conditions are not covered by warranty. |
| 3) Keep unit at least 15' from exterior doors, overhead HVAC vents, or any air curtain disruption. |
| 4) Do not expose unit to direct sunlight or any heat source (ovens, fryers, etc.). |

| REGULATORY | |
|------------|---|
| All Models | ETL Listed to UL 197 ETL Listed to CAN/CSA 22.2 No. 109 ETL Sanitation to NSF 4 |



End Caps - BOX Heated Self-Service Case 32"D

NOTE: ALL DIMENSIONS APPROXIMATE



ELECTRICAL JUNCTION BOX
(SUPPLIED WITH 6" LEADS OR POWER CORD).



LOCATION OF DRAIN TUBE FOR REMOTE REF.
ONLY (SUPPLIED WITH 3/4" OR 1 1/2" PVC TUBE).



REFRIGERATION LINE CONNECTION.



REMOTE FLOOR SINK & UTILITIES
ACCESS AREA.



SELF-CONTAINED CASE SERVICE ACCESS AREA.



DRY CASE SERVICE ACCESS AREA.

