

G Series - GHSV 56"H Refrigerated High-Capacity Service Case w/ Vertical Glass

DIMENSIONS / SHIPPING				
Model	L"	L1"	L2"	Est Wt (lbs)
GHSV456RLB	48.750	51.000	3.625	N/A
GHSV556RLB	60.500	62.750	3.625	N/A
GHSV656RLB	73.125	75.375	3.625	N/A
GHSV856RLB	97.500	99.750	3.625	N/A
GHSV1256RLB	146.250	148.500	101.125	N/A

ELECTRICAL															
Model	System Circuit Volts			Ph	Frq	Rated Load Amps	Min Cir Amps	Max OCP Amps	Watts	Wires	NEMA Plug	Amps Lights	Amps Fans	Amps Anti-Sweats	Amps Misc/Refrig/Heat
GHSV456RLB	Remote(DX)	Circuit #1	110-120	1	60	1.84	15	15	83	2+G	Leads Multiple	0.70	0.30	0.84	N/A
GHSV556RLB	Remote(DX)	Circuit #1	110-120	1	60	2.94	15	15	142	2+G	Leads Single	1.40	0.62	0.92	N/A
GHSV656RLB	Remote(DX)	Circuit #1	110-120	1	60	2.96	15	15	158	2+G	Leads Multiple	1.40	0.60	0.96	N/A
GHSV856RLB	Remote(DX)-Type I Env	Circuit #1	110-120	1	60	3.76	15	15	176	2+G	Leads Multiple	2.80	0.60	1.06	N/A
	Remote(GLYCOL)-Type I Env	Circuit #1	110-120	1	60	4.51	15	15	131	2+G	Leads Multiple	2.80	0.60	1.06	0.05
GHSV1256RLB	Remote(DX)	Circuit #1	110-120	1	60	4.95	15	15	265	2+G	Leads Multiple	2.10	0.90	1.95	N/A
	Remote(R744 T)	Circuit #1	110-120	1	60	4.95	15	15	265	2+G	Leads Multiple	2.10	0.90	1.95	N/A

REFRIGERATION														
Model	Zone	Section	System	Envt	REMOTE REFRIGERATION					GLYCOL / R744 REFRIGERATION				
					SST (°F)	Conv. Rack BTUH	Para. Rack BTUH	Defrost Interval (Hrs)	Defrost Duration (Mins)	Total GPM	Pressure Drop (psi)	Concent (%)	Liquid Temp (°F)	
GHSV456RLB	All	Main	Remote-DX	Type I	24	2,030	1,880	4.00	30.00	N/A	N/A	N/A	N/A	
GHSV556RLB	All	Refrigerator	Remote-DX	Type I	20	2,916	2,700	4.00	30.00	N/A	N/A	N/A	N/A	
GHSV656RLB	All	Main	Remote-DX	Type I	20	3,154	2,920	4.00	30.00	N/A	N/A	N/A	N/A	
GHSV856RLB	All	Main	Remote-DX-Type I Env	Type I	20	4,061	3,760	4.00	30.00	N/A	N/A	N/A	N/A	
	All	Main	Remote-Glycol-Type I Env	Type I	N/A	4,061	3,760	4.00	45.00	1.25	4.00	35%	20.00	
GHSV1256RLB	All	Main	Remote-DX	Type I	20	6,048	5,600	4.00	30.00	N/A	N/A	N/A	N/A	
	All	Main	Remote-R744 TRANSCRITICAL	Type I	20	6,048	5,600	4.00	30.00	N/A	N/A	N/A	N/A	

INTENDED ENVIRONMENT		
Type I - Designed to operate in ambient conditions of 75°F with 55% relative humidity unless noted otherwise under Envt above.		
WARMEST AVERAGE PRODUCT TEMP & INTENDED USE OF ZONES		
Zone	Temp (°F)	Intended Use
1	40	Unpackaged refrigerated products

IMPORTANT NOTES
1) Units must be shimmed during installation to ensure the unit is level and plumb.

REGULATORY	
All Models	Accordance with AHRI Std 1200 ETL Listed to UL 471 ETL Listed to CAN/CSA 22.2 No. 120 ETL Sanitation to NSF/ANSI 7



In Accordance with
AHRI Std 1200

